



## Typical Inspection Data:

Density @ 20°C	0.841 g/cm <sup>3</sup>
Viscosity @ 100°C	8.2 cSt
Viscosity @ 40°C	41 cSt
Viscosity Index	180
Viscosity CCS @ -35°C	5500 cP
T.B.N.	7.9 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.09%
Calcium	0.11%
Phosphorus	0.08%
Colour	Brown
Flash Point (Closed Cup)	210°C
Pour Point	-48°C

## Eco-Z 0W-20

### Fully Synthetic

#### Official Approvals:

MB-Approval 229.72

#### Recommended by Comma for applications requiring:

MB 229.71; Chrysler MS-12145; FIAT 9.55535-GSX; Ford WSS-M2C947-B1, Ford WSS-M2C962-A1; BMW LL17FE+, BMW LL14FE+; OV 040 1547 – A20; STJLR.03.5006; ILSAC GF-5, ILSAC GF-6A; ACEA C5, C6; API SP, SP RC

#### Product Features:

- Fully synthetic, high performance 0W-20 oil for modern petrol & diesel engines.
- Provides excellent low speed pre-ignition (LSPI) protection and protects after-treatment systems including petrol particulate filters.
- Helps to deliver high fuel economy as per latest OEM requirements.
- For the latest Opel/Vauxhall, Mercedes Benz and BMW cars requiring high level of fuel economy and LSPI protection.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 25.05.2023