



Typical Inspection Data:

Density @ 20°C	0.840 g/cm ³
Viscosity @ 100°C	8.0 cSt
Viscosity @ 40°C	40.0 cSt
Viscosity Index	178
Viscosity CCS @ -35°C	5000 cP
T.B.N.	9.5 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.12%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

Eco-FO 0W-20

Fully Synthetic

Official Approvals:

Approved by OPEL Vauxhall to meet OV 040 1547 - A20; verified by Jaguar Land Rover to meet the requirements of STJLR.03.5006

Recommended by Comma for applications requiring:

ACEA C5, ACEA C6; API SN Plus, API SP; Dexos D; Ford WSS-M2C952-A1; MB 229.71

Product Features:

- Fully synthetic, low viscosity engine oil specifically developed for Ford EcoBlue diesel engines where Ford WSS-M2C952-A1 is required.
- Provides excellent low speed pre-ignition (LSPI) protection, delivers high fuel economy performance, whilst maintaining exceptional wear protection.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 23.03.2023