



Typical Inspection Data:

Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	11.1 cSt
Viscosity @ 40°C	61 cSt
Viscosity Index	177
Viscosity CCS @ -30 °C	3600 cP
T.B.N.	8.3 mg KOH/g
Sulphated Ash Mass	0.90%
Zinc	0.10%
Calcium	0.13%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

X-Flow Type X 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

API SN; ILSAC GF-5; Dexos 1:2015

Product Features:

- Fully synthetic, high performance 5W-30 oil for modern petrol engines.
- Provides low speed pre-ignition (LSPI) protection, particularly for small displacement turbo-charged engines. Aids fuel economy.
- Quick cold weather starting for ultra-fast protection.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

UPDATED: 15-12-2021