



Typical Inspection Data:

Density @ 20°C	0.847 g/cm ³
Viscosity @ 100°C	7.9 cSt
Viscosity @ 40°C	42 cSt
Viscosity Index	162
Viscosity CCS @ -30°C	4000 cP
T.B.N.	8.1 mg KOH/g
Sulphated Ash Mass	0.10%
Zinc	0.09%
Calcium	0.19%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

X-Flow Type B 5W-20

Fully Synthetic

Recommended by Comma for applications requiring:

FORD WSS M2C948-B, WSS-M2C925-A,
WSS-M2C925-B; ACEA C5; API SN

Product Features:

- Fully synthetic, high performance 5W-20 oil for the latest Ford Ecoboost engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 06-12-2018